



PATENT ABSTRACTS OF JAPAN

(11) Publication number: **04126081 A**(43) Date of publication of application: **27.04.1992**

(51) Int. Cl. **C12N 15/02**
C12M 1/42, C12N 5/12, C12N 13/00

(21) Application number: **02284774**
 (22) Date of filing: **23.10.1990**
 (30) Priority: **20.06.1990 JP 02161964**

(71) Applicant: **P C C TECHNOL:KK**
 (72) Inventor: **SAKAMOTO KAZUCHIKA**
IIDA KUMIKO
KOYANO TAKASHI
FUJITA KAZUHIRO

(54) **CELL FUSION SYSTEM AND FUSED CELL
 SELECTION SYSTEM**

(57) Abstract:

PURPOSE: To enable efficient, quick and pure selection of fused cell by supplying a liquid to a flow-type cell-fusion chamber to introduce cells into the chamber and applying electric stimulation to the cell.

CONSTITUTION: Two kinds of cells A and B are mixed with each other and put into a sample bottle 2 to obtain a mixed liquid 12. The liquid 12 is transferred through a liquid-feeding system 13a to a flow chamber 14 and excited with pulses generated from a pulse generator 15b, etc., and having a pulse width of 10 μ -sec to 10m-sec and a field strength of ≤ 2 kV/cm to effect the cell-fusion. The fused cell 17 is transferred to a fused cell collection bottle 16 and the liquid is successively supplied to a flow cytometer 19 according to the pre-set condition. The liquid 17 and a sheath liquid flow are ejected at a high speed from the flow cytometer 19 through a small-nozzle flow-cell tip. A laser beam is radiated to the liquid flow and the scattering light, etc., generated by the cell is detected by a detector to

discriminate a heterocaryon from the other cells. The liquid droplet containing the heterocaryon is electrified, deflected and collected in the object fused cell collection bottle 20 to obtain a suspension 21 of the objective fused cell.

COPYRIGHT: (C)1992,JPO&Japio

